

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application. Please amend claims 1, 2 and 5 and add new claim 6 as follows:

1. (Currently Amended) An image pick-up device comprising:

image signal pick-up means for picking up an image signal with a varied frame-rate;

[[image signal generation]] frame-addition processing means for generating a first image signal, [[of a]] from the variable frame-rate picked-up image signal, with a selected output frame rate;

frame rate conversion means for [[matching]] converting a frame rate of [[the first]] a second image signal and a frame rate of a second image signal supplied from an outside with each other to the output frame rate of the first image signal; and

signal generation means for generating a monitor image signal by using the first image signal and the second image signal ~~whose frame rates are matched with each other by the frame rate conversion means.~~

2. (Currently Amended) The image pick-up device according to claim 1, wherein the frame [[rate conversion]]-addition processing means [[matches the]] generates the output frame rate of the second image signal with the frame rate of the first image signal by adding a selected number of frames to the image signal.

3. (Original) The image pick-up device according to claim 1, wherein the signal generation means uses the first and second image signals to generate, as the monitor image

signal, an image signal of an image in which an image based on the first image signal and an image based on the second image signal are mixed.

4. (Original) The image pick-up device according to claim 1, wherein the signal generation means uses the first and second image signals to generate, as the monitor image signal, an image signal of an image in which a part of an image based on the first image signal is replaced by an image based on the second image signal.

5. (Currently Amended) An image pick-up device comprising:
pick-up portion that picks up an image signal with a varied frame-rate;
[[an image signal generation]] frame-addition processing portion that generates a first image signal, [[of a]] from the variable frame-rate picked-up image signal, with a desired output frame rate;

a frame rate conversion portion that [[matches]] converts a frame rate of [[the first]] a second image signal ~~and a frame rate of a second image signal~~ supplied from an outside [[with each other]] to the output frame rate of the first image signal; and

a signal generation portion that generates a monitor image signal by using the first image signal and the second image signal ~~whose frame-rates are matched with each other by the frame-rate conversion portion.~~

Don E.
11/20/07

6. (New) ~~The~~ image pick-up device according to claim 5, wherein the frame-addition processing portion generates the output frame rate of the first image signal by adding a predetermined number of frames to the image signal.